

ROTADAIRON Machine Models	*POWER REQUIREMENTS At .5 mph (.8kph)(low number) At 1 mph (1.6kph)(high number)	WORK width	MAXIMUM work depth (adjustable)	WORKING OFFSET Right of center	TOTAL weight
---------------------------------	--	---------------	---------------------------------------	--------------------------------------	-----------------

#### SUBCOMPACT UNITS FOR SKID STEER AND MINI SKIDS (Hydraulically driven)

STH 36	7.9 to 11.8 GPM + 2900-3625psi	38" (96cm)	5.5" (14cm)	24" (61cm)	584lb (265kg)
STH 42	10.5 to 14.5 GPM + 2900-3625psi	43.25" (1m)	5.5" (14cm)		628lb (285kg)
RDH 52	18.5 to 31.7 GPM + 3045-4350psi	52.75" (1.3m)	5.5" (14cm)		992lb (450kg)
RDH 60	18.5 to 31.7 GPM + 3045-4350psi	59" (1.5m)	5.5" (14cm)		1102lb (500kg)
RDH 52 F	Equipped with cast iron packer roller				1223lb (555kg)
RDH 60 F					1378lb (625kg)

#### COMPACT SOIL RENOVATORS

STONY 75	15 to 18 PTO HP	29.5" (76cm)	5 ½" (14cm)	20" (50.8cm)	590lb (267kg)
STONY 90	18 to 25 PTO HP	38" (96.3cm)	5 ½" (14cm)	25" (63.5cm)	628.3lb (285kg)
STONY 115	20 to 25 PTO HP	43.25" (1.1m)	5 ½" (14cm)	25" (63.5cm)	749.5lb (340kg)
RD 100	22 to 35 PTO HP	43.75" (1.1m)	5 ½" (14cm)	27" (69.8cm)	892lb (405kg)
RD 130	25 to 45 PTO HP	52.75" (1.3m)	5 ½" (14cm)	33" (83.8cm)	992lb (450kg)
RD 145	30 to 50 PTO HP	59" (1.5m)	5 ½" (14cm)	31.5" (80cm)	1135lb (463kg)
RD 130F	Equipped with cast iron packer roller				1157.4lb (525kg)
RD 145F					1355.8lb (615kg)

#### STANDARD DUTY SOIL RENOVATORS

RD 150	45 to 60 PTO HP	59" (1.5m)	6.25" (16cm)	37" (94cm)	1759lb (798kg)
RD 180	50 to 70 PTO HP	69.75" (1.8m)	6.25" (16cm)	37.5" (95.25cm)	2017lb (915kg)
RD 200	55 to 80 PTO HP	78" (2m)	6.25" (16cm)	na	2127lb (965kg)
RD 250	70 to 95 PTO HP	98" (2.5m)	6.25" (16cm)	na	2500lb (1134kg)
RD 150FH	Equipped with cast iron packer roller				2105lb (955kg)
RD 180FH					2469lb (1120kg)
RD 200FH					2641lb (1198kg)
RD 250FH					3127lb (1421kg)

#### HEAVY DUTY SOIL RENOVATORS (*single drive*)

RX 200	80 to 100 PTO HP	80.5" (2m)	8" (20cm)	na	3575lb (1622kg)
--------	------------------	------------	-----------	----	-----------------

#### HEAVY DUTY SOIL RENOVATORS (*double drive*)

RX 250	110 to 150 PTO HP	99.5" (2.5m)	8.5" (22cm)	na	4263lb (1934kg)
RX 300	110 to 160 PTO HP	120" (3m)	8.5" (22cm)	na	4832lb (2192kg)
RX 370	130 to 180 PTO HP	144" (3.7m)	8.5" (22cm)	na	5509lb (2499kg)
RX 250F	Equipped with cast iron packer roller				5036lb (2280kg)
RX 300F					5705lb (2588kg)
RX 370F					6565lb (2978kg)

\*HP and GPM requirements based on selected ground speed and site conditions.